

Outdoor Commercial Intelligent LED Poster

A small-sized outdoor integrated display poster. With simple yet elegant exterior design and vivid displaying effect, the poster can be more eye-catching thus to promote advertising effectiveness.

Water-proof aluminum cabinet and automatic ventilation system enable these stands to stay out in various working environments. Two-sided design offers customers more choices, which the poster can be customized into full-colour LED display on both sides or full-colour LED display on front side and light box with backlight support on back side.

Your first choice for volume outdoor poster applications.



FEATURES

- Automatic brightness adjustment
- High IP rating
- Superior heating dissipation
- Two-sided advertising display
- Two-sided cover, hydraulic system, front maintenance
- Tempered glass, upgraded safeguard
- Aluminum cabinet, water-proof
- Long working life
- Light weight, convenient transportation
- Low consumption, power saving

ADVANTAGES

- More application environments
- Better advertising effectiveness
- Wider range of audience
- Maximize profits
- Lower operating costs
- Low investment and high return
- Enhanced ornamental function



Outdoor Commercial Intelligent LED Poster

Our LED displays are 100% Australian made. Stunning visuals, easy installation, and ultimate performance. Displays that engage and inspire.



ITEM TYPE	TECHNICAL PARAMETERS		
	3.9mm	5.2mm	6.25mm
Pixel Pitch(mm)	3.9	5.2	6.25
LED Type	SMD	SMD	SMD
Brightness (cd/m2)	5000	5000	5000
Refresh Rate (Hz)	≥1920	≥1920	≥1920
Power Consumption (Max/Ave) (W/display) Single	1750/750	1600/700	1600/700
Power Consumption (Max/Ave) (W/display) Double	3400/1450	3100/1350	3100/1350
Module Resolution (px)	64×64	48×48	40×40
Module Size (mm)	250×250	250×250	250×250
Display Resolution (px)	320×448	240×336	200×280
Display Size (mm)	1250×1750	1250×1750	1250×1750
Overall Dimension (mm)	1450×2300×230	1450×2300×230	1450×2300×230
Weight (Single/Double) (kg)	220/280	220/280	220/280
IP Rating	IP54	IP54	IP54
Maintenance	Front	Front	Front
Operating Temperature/Humidity (C°/RH)	-30~50/10~90%	-30~50/10~90%	-30~50/10~90%



GET IN TOUCH

Phone: +61 1300 841 542

Email: sales@aurorasignage.com.au

Website: www.aurorasignage.com.au

Showroom: 60 Grove Avenue, Marleston SA 5033

ABN 22 620 120 836